

Specs Slitter

SLITTER		Slitter 1	Slitter 2	Slitter 3	Slitter 4	Slitter 5	Slitter 6	Slitter 7	Slitter 8
Thickness		0.30 – 3.28 mm	0.23 – 1.60 mm	0.60 – 6.30 mm	0.20 – 1.20 mm	0.20 – 1.60 mm	0.60 – 6.50 mm	0.50 – 2.00 mm	0.18 – 0.65 mm
In (Coil)	Width	300 – 1,524 mm	300 – 1,300 mm	300 – 1,524 mm	50 – 500 mm	300 – 1,300 mm	300 – 1,600 mm	90 – 450 mm	600 – 1,200 mm
	Weight	20 mt max.	15 mt max.	20 mt max.	25 mt max.	15 mt max.	25 mt max.	2 mt max.	10 mt max.
	Internal Diameter	508 – 610 mm	508 or 610 mm	508 – 610 mm, or 762 mm	508 mm	508 mm	508 or 610 mm	508 mm	508 mm
	Outside Diameter	1,810 mm max.	1,800 mm max.	1,810 mm max.	1,200 mm max.	1,800 mm max.	2,000 mm max.	1,000 mm max.	1,500 mm max.
Out (Strip)	Width	25 – 1,524 mm	50 – 1,300 mm	50 – 1,524 mm	20 – 500 mm	25 – 1,300 mm	40 – 1,600 mm	8 – 450 mm	50 – 1,200 mm
	Weight	20 mt max.	15 mt max.	20 mt max.	2.5 mt max.	15 mt max.	25 mt max.	2 mt max.	10 mt max.
	Internal Diameter	508 or 610 mm	508 or 610 mm	508 or 610 mm	508 mm	508 mm	508 or 610 mm	508 mm	508 mm

SERVILAMINA SUMMIT
MEXICANA S.A. DE C.V.